

## FUMED SILICA SN-200

Product Name: Fumed Silica Molecular Formula: Sio2 Cas No: 7631 -86- 9

**Product Standard:** Gb/t 20020 - 2013

## **Physical And Chemical Properties:**

Melting Point / Freezing Point: 1750°C Vapour Pressure: 32hPa (25°C) Relative Density (Water=1): 0.22

**Appearance:** White Powder

Technological Index		
ltem	Index	
Surface Area (m2/g)	HS - 150 150~185	HS - 200 185~225
Ignition loss /% ≤	2.5	
Silicone oxide /% ≤	99.8	
Aluminium oxide /(mg/Kg) ≤	400	
Titanium Dioxide(mg/Kg) ≤	200	
Ferric Oxide/ (mg/Kg) ≤	30	
Content of Carbon /% ≤	0.2	
Chloride/(mg/kg) ≤	250	
PH Value in Aqueous Dispersion	3.7~4.5	
Volatilization Loss (105°C) /% ≤	2	
Tap density(g/dm3)	30~60	
45µm Sieve Residue /% ≤	250	

## **Properties and Uses**

It is white, loose, amorphous, non-toxic and non-odorous nonmetal oxide. Due to the nanometer effect, it has excellent properties, such as reinforce, bodying, thixotropy, insulation and others. Therefore, it can be widely used in the rubber, plastic, paint coating, adhesive, seals and other polymer industrial area.

## Package, Storage and Handling

10kg/paper bag. Keep in a cool, dry, well-ventilated place. Store away from incompatible substances such as oxidizing agents.



www.sinoxe.com
info@sinoxe.com